

Customer Engagement Kiosk

T10 KIOSK



The Right Customer Service Solution for Your Business

Today's customers want to get the right information at the right time for decision-making. Business loses Customers everyday through the simple act of making customers wait.

By delivering right service in line with customer expectations, your business will increase customer loyalty, satisfaction and sales.

With the T10 Kiosk, you can cater to your customer's every need to enhance customer experience.

T10 Kiosk Specification

PERFORMANCE CHARACTERISTICS	CPU	2.2GHz Octa-Core processor
	Operating System	Android 14
	Memory	6GB RAM / 128GB Flash
PHYSICAL CHARACTERISTICS	Dimensions (L x W x D)	249.20 x 158.80 x 30.2 mm
	Display	10.36 inch, 2000x1200 IPS
	Touch Panel	Capacitive multi-touch
	Power	9V DC; 802.3af/at Power-over Ethernet (PoE / PoE+)
	Interface	1 x USB Type C (2.0) (OTG) DC-IN 1ea 1 x Ethernet w/ 802.3at PoE/PoE+ RJ45 1 x USB 2.0 Type A Host 3.5 mm connectorjack : Audio In(Headset + MIC); (TBD) SD Card Slot up to 2TB Reset Button 1ea; (TBD) Integrated standard VESA mount (75 x 75)
	Expansion Slot	User accessible MicroSD supports up to 2TB
	Keypad	On-screen keypad
	Audio	1 microphone; Two front speakers (3W total); (TBD)
WIRELESS LAN	Radio	IEEE 802.11 a/b/g/n/ac, support 2.4G and 5G dual frequency
	Data Rates	5GHz: 802.11a/n/ac — up to 433 Mbps 2.4GHz: 802.11b/g/n — up to 150 Mbps
	Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2); EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC; Enhanced Open (OWE)
WIRELESS PAN	Bluetooth	Bluetooth v5.2, BLE

Bluebird Inc.

(Corporate Headquarters) 3F, 115, Irwon ro, Gangnam gu, Seoul, Republic of Korea. Postal#06355 /Phone. +82.1577.0778 Fax. +82.2.6499.2242

Copyright © 1995-2024 Bluebird Inc. All rights reserved. Bluebird Inc. is the designer and manufacturer of Bluebird handheld mobiles. Bluebird logo is registered trademark of Bluebird Inc.

T10 Kiosk Specification(Continued)

DATA CAPTURE	Integrated Scanner	All major 1D/2D symbologies
		EAN 13 (13mil): 60mm-350mm
		Code 39 (5mil): 40mm-150mm
		PDF417 (6.7mil): 50mm-125mm
		DataMatrix (10mil): 45mm-120mm
		QR (15mil): 30mm-170mm
Camera	Front : 8MP Fixed Focus	
NFC; (TBD)	(Optional) ISO 14443 Type A and B; FeliCa and ISO 15693 cards; Card Emulation via Host;	
SENSOR	Sensors	Ambient Light, Proximity, eCompass, Accelerometer, Gyroscope
USER ENVIRONMENT	Operating Temp.	-10° C to 50° C
	Storage Temp.	-20° C to 60° C
	Humidity	60% non-condensing
	IP Rating	IP54 (Front only)
	Electrostatic Discharge(ESD)	+/-10kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
MOUNTING OPTIONS	Integrated standard VESA mount; conforms to the VESA 75 mm x 75 mm mounting standard for attachment of third party, off-the-shelf mounting solutions; four (4) M4 x 8 mm max insert distance	
SOFTWARE	BOS™ Provisioning, Staging, Kiosk, NEST, Wi-Fine (WIFI analyze application)	
ACCESSORIES	Power Adapter & AC Line Cord VESA standard Wall / Pole / Desktop mountingbracket Communication cable forPC Compatible POE injector	

* Specifications subject to change without notice.

Bluebird Inc.

(Corporate Headquarters) 3F, 115, Irwon ro, Gangnam gu, Seoul, Republic of Korea. Postal#06355 /Phone.
+82.1577.0778 Fax. +82.2.6499.2242

Copyright © 1995-2024 Bluebird Inc. All rights reserved. Bluebird Inc. is the designer and manufacturer of Bluebird handheld mobiles. Bluebird logo is registered trademark of Bluebird Inc.