











Ultimate Rugged Mobile Computer

VX500



- Rapid working process through the latest OS and powerful CPU
- Fast and stable communication network
- Powerful durability in the harshest environments
- Quick data capturing through high performing barcode scanner
- Long-lasting battery power
- Mobile device management software eco-system BOS™ support



 OS Android 10 Android 11	 Performance Octa-Core Processor	 Wireless Wi-Fi, Bluetooth 5.0	 Battery User Replaceable, Smart Battery	 Scanning 1D & 2D imager
 Sealing IP68	 Operating Temp -4°F to 131°F -20°C to 55°C	 Camera 13MP Autofocus with flash	 Display 5" HD (1280 x 720)	 Drop Resistance 1.5m/4.9ft MIL-STD-810G 1.8m/5.9ft. MIL-STD-810G (w Rugged Boot)

Key Features

Best in enterprise-class Qualcomm Snapdragon™ 660 (Octa-Core 2.2GHz (Max. 2.45GHz)) and Android 10 and Android 11 OS increase work efficiency, supporting users' work process in prompt and stable ways. Users can switch their apps on the display quickly by Universal Flash Storage (UFS) memory which increases the speed of operation.

Fast, stable communication network support VX500 provides superior voice quality, stable connectivity, and clear communication based on Bluebird's innovative technology. The device also provides improved Wi-Fi speed and broader range of networking with applying MU-MIMO technology.

Powerful durability in the harshest environments Usability-proven in touch and harsh environments Bluebird TankSmith® Technology and Corning® Gorilla® Glass 5 enhance durability of the device meeting 1.8m of drop spec MIL-STD 810 (with Rugged Boot) and IP68 Sealing rate. VX500 provides flexible multi-touch including glove, wet, and stylus as well as the best outdoor readability that you can see the display under the very bright sunlight.

High performance barcode scanner for quick data capture The latest scan engine provides superior wide range up to 24-inch/60cm for 1D/2D barcodes, labels, and documents. Workers can scan even poor quality, damaged and dirty barcodes. It delivers lightning fast barcode scan with motion tolerance providing fast scan on pressing the scan button. Large sweet spot makes workers can scan easily with point-and-shoot simplicity.

Long-lasting battery power (Hotswap support) User replaceable battery with high capacity of 4350mAh gets you free from worrying about re-charge. As hotswappable battery it supports work continuity even when unexpectedly detached and prevents data loss. With Bluebird BOS™ (Business Optimizing Solution) Power Manager solution, it enables to manage battery life status which delivers replacement period for aged batteries.

Mobile device management software eco-system BOS™ (Business Optimizing Solution) Bluebird BOS™ (Business Optimizing Solutions) provides various features optimized for use of enterprise device from app development, device deployment, to business performance management as an integrated solution system. With BOS™ you can implement integrated management for VX500 in an efficient way.

Verticals & Applications

Retail

- Price/Inventory Check
- Inventory management
- mPOS (Mobile POS)
- BOPIS (Buy online, Pick up in store)
- Loyalty management
- Sales assistance
- Voice communication
- Electronic coupon
- Coupon verification

Field Service

- Asset management
- Invoicing

T&L

- PoD (Proof of Delivery)

Healthcare

- Patient management
- Staff communication

Restaurant & Hospitality

- Order management
- mPOS (Mobile POS)

Government/Public Sector

- ID Verification/ Ticketing

BOS™ Solutions & Software

- BOS™ Provisioning
- BOS™ Staging
- BOS™ Kiosk
- BOS™ Enterprise Keyboard
- BOS™ VoIP, PTT, PTT Express
- BOS™ EMM
- BOS™ Wi-Fine™
(WIFI analyze application)
- BOS™ Power Manager™

3rd Party Solutions Integration

- EMM : Airwatch(Vmware workspace ONE), MobileIron, Mobicontrol, IBM Mass360, XenMobile
- PTT : MCPTT, IPPTT

Specifications

PERFORMANCE CHARACTERISTICS	
CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz (Max. 2.45GHz)
OS	Android 10 Android 11
Memory	4GB, 6GB RAM 32GB, 64GB Flash (UFS)

PHYSICAL CHARACTERISTICS	
Dimension (L x W x D)	158.26 x 75.8 x 14.9mm
Weight	246g
Display	5.0" HD (1280 x 720), TFT-IPS
Touch panel	Corning® Gorilla® Glass 5 Capacitive multi-touch (Stylus, Glove, Wet)
Backlight	LED backlight
Power	User replaceable Battery 3.85V / 4,350 mAh BOS™ PowerManager Station
Hotswap	Support
Expansion Slot	MicroSD 32GB SDHC, up to 128GB SDXC Hybrid Dual SIM Slot
SIM / SAM	(2 Nano SIM or 1 Nano SIM/1 Micro SD) - 1 Nano SIM is supported by micro SD Card Slot Single SAM (Optional)
Interface	USB Type C Connector (USB 2.0) Docking Connector (Charging)
Notification	Audible tone; multi-color LEDs; vibration
Keypad & Button	Dedicated PTT Buttons; Dedicated Emergency Button; Power Button; Volume up/down Buttons; Home, Back, Menu Buttons
Voice & Audio	High-quality dual speakers 4W (2W x 2) Dual noise-cancelling microphones; 3.5mm headset jack
PTT Hot Key	Dedicated PTT Button

WIRELESS WAN DATA AND VOICE COMMUNICATIONS	
Radio Frequency Band	(Optional) Korea : - LTE : B1(2100MHz), B3(1800MHz), B5(850MHz), B7(2600MHz), B8(900MHz), B28R(700MHz) - WCDMA : B1(2100MHz) EMEA (Optional-TBD) - LTE : B1(2100MHz), B3(1800MHz), B5(850MHz), B7(2600MHz), B8(900MHz), B20(700MHz) - WCDMA : B1(2100MHz), B8(900MHz)
GPS	A-GPS, GLONASS, BEIDOU, Galileo

WIRELESS LAN	
Radio	IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/w IPv4, IPv6, 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac – up to 866.7 Mbps 2.4GHz: 802.11b/g/n – up to 300 Mbps
Security and Encryption	WEP (40 or 104bit); WPA/WPA2 Personal (TKIP and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS(PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP.EAP-PWD Data in Motion : FIPS 140-2 Level 1 Data at Rest : FIPS 140-2 Level 1

WPAN	
Bluetooth	Bluetooth 5.0, BLE ,Class 2

DATA CAPTURE	
Barcode	SE4710 - 1D & 2D Laser - Field of View (Horizontal : 42°, Vertical : 28°) - Immune to direct light from the sun : 107,639 lux
Biometrics	Fingerprint (via Home button) (Optional)
Camera	Rear – 13MP Autofocus with flash Front – 5MP fixed
NFC	ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards, MiFare

SENSOR	
Light Sensor	Ambient Light Automatically adjusts display backlight brightness
Motion Sensor	Proximity, Accelerometer, E-Compass, Gyro, barometer

USER ENVIRONMENT	
Operating Temp.	-4°F to 131°F / -20°C to 55°C
Storage Temp.	-22°F to +158°F / -30°C to +70°C
Humidity	95% non-condensing
Drop Spec.	1.5m(4.9ft.) MIL-STD-810G; Multiple 1.5m(4.9 ft.) drops to tile over concrete at room temperature 1.8m(5.9ft.) MIL-STD-810G; Multiple 1.8m(5.9ft.) drops on concrete at room temperature with the rugged boot accessory
Sealing	IP68
Tumble Spec.	300 1.6 ft./0.5m tumbles; meets and exceeds IEC tumble specification 1,500 1.6 ft./0.5m tumbles; meets and exceeds IEC tumble specifications with the rugged boot accessory
Vibration	4G peak, 5 Hz to 2 kHz, 1 hour duration per axis
Thermal Shock	-40° C to 70° C / -40° F to 158° F rapid transition 10 cycles (1 cycle = 1.25 hours at -40° C and 1.25 hours at 70° C)
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

ACCESSORIES	
Accessories	1) 1 or 4 slot charging cradle (Includes a bay for Spare Battery Charging) 2) 1 or 4 slot ethernet cradle (Includes a bay for Spare Battery Charging) 3) Rugged boot & Handstrap 4) Protective Film 5) Trigger Handle 6) UHF RFID Reader Sled (w/ RFR900)

* Specifications are subject to change without notice.

Bluebird Inc.(Corporate Headquarter)

3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea,
Postal#06355 Phone. +82-1577-0778 Fax. +82.2.6499.2242
Copyright © Bluebird Inc. All rights reserved.

Bluebird Inc. is the designer and manufacturer of Bluebird handheld mobiles.
Bluebird logo is registered trademark of Bluebird Inc.
All other trademarks are property of their respective owners.